

SAFETY DATA SHEET


Revision Date: 12/16/14

This Safety Data Sheet may be used to comply with OSHA's Hazard Communication Standard, 29 CFR 910.1200 and ANSI Z400-1-1998.

Section 1: Identification of the Product and of the Company

| | |
|---------------------|---|
| Product Code | MA GOLD PART B |
| Trade Name | Paint Sealant |
| Product Description | Mixture of hydrocarbons and resins |
| General Use | Paint Sealant |
| Manufacturer | Commodore Coatings |
| Address | 11002 Trade Road Richmond Virginia 23236 |
| Phone | (804) 794-1992 (8am-4pm M-F) |
| Toll Free | (800) 747-1992 |
| Chemtrec | (800) 262-8200 (24 hour) |
| Outside U.S. | (703) 741-5500 |

Section 2: Hazards Identification

| | | |
|----------------------------|---|---|
| OSHA Hazards | Irritant | |
| Signal Word | Warning | |
| Hazard Statement(s) | H302 | Harmful if swallowed |
| | H315 | Causes skin irritation |
| | H320 | Causes eye irritation |
| Pictogram(s) |  | |
| Precautionary Statement(s) | P305 +351 +338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so – continue rinsing. |

Section 3: Composition/Information on Ingredients

| Component | CAS | Weight % |
|-----------------------------|-------------|----------|
| Water | 7732-18-5 | >50.00 |
| Aliphatic Hydrocarbon | 8052-41-3 | >10.00 |
| Morpholine | 110-91-8 | <1.50 |
| Kaolin Clay | 66402-68-4 | |
| Dimethyl Polysiloxane | 63148-62-9 | |
| Carnuba Wax | 8015-86-9 | |
| 2-Aminoethyl Siloxane | 102782-92-3 | |
| Magnesium Aluminum Silicate | 1327-43-1 | |
| Diatomaceous Earth | 7631-86-9 | |
| Fatty Acid | 112-80-1 | |

| | |
|------------------------------|------------|
| Quaternary Ammonium Compound | 68308-67-8 |
| Polyacrylic Acid | 9007-16-3 |
| Acrylic Polymer | 75760-37-1 |
| Triethanolamine | 102-71-6 |

Hazardous Components

(OSHA 29 CFR 1910.1200)

Aliphatic Hydrocarbon
Morpholine

The specific chemical identities and/or exact percentage concentration of composition may have been withheld as a trade secret.

Section 4: First Aid Measures

| | |
|------------------|--|
| Inhalation | None known |
| Skin Contact | Wash with soap and water. Rinse thoroughly. |
| Eye Contact | Rinse with water for 15 minutes. Get medical attention if irritation persists. |
| Ingestion | Do not induce vomiting. Get medical attention. |
| Symptoms/Effects | None known |

Section 5: Firefighting Measures

| | |
|-------------------------------|--|
| Hazardous Combustion Products | Possible oxides of carbon. |
| Firefighting Instructions | Use water to must to cool fire exposed drum. |
| Firefighting Equipment | Bunker gear and SCBA. |

Section 6: Accidental Release Measures

| | |
|-------------|--|
| Land Spill | Avoid run off into storm sewers or ditches by containment with sand or absorbent material. |
| Water Spill | Remove from water with suitable absorbent material. |

Section 7: Handling and Storage

| | |
|-------------------------------|--|
| Precautions for Safe Handling | Take normal care to prevent prolonged skin contact. |
| Precautions for Safe Storage | Keep from freezing or from heating about 110°F. Store in original container. |

Section 8: Exposure Controls/Personal Protection

| | |
|-----------------------|---------------------------------|
| Components | OSHA PEL & ACGIH TLV |
| Aliphatic Hydrocarbon | 100 ppm |
| Morpholine | 20 ppm |

| | |
|------------------------------|---|
| Engineering Controls | The use of mechanical ventilation is not needed under normal conditions. |
| Personal Protective Measures | Not needed under normal conditions. The use of rubber gloves and respirator is recommended for prolonged contact. |

Section 9: Physical and Chemical Properties

| | |
|---|--|
| Appearance | Semi viscous, light grey to off white cream |
| Odor | Mild Solvent |
| Odor Threshold | Not available |
| Vapor Pressure | Not available |
| Vapor Density | Not available |
| Specific Gravity | 1.00 @ 70°F |
| pH | Not available |
| Viscosity | 16,000 – 23,000 cps (Brookfield Viscometer: spindle 5 @ 20 rpm @ 70°F) |
| Weight/Gallon | 8.34 lb/gal |
| Freezing Point | Not available |
| Boiling Point | Not available |
| Solubility in Water | Insoluble |
| Percent Volatile | Not available |
| Flash Point and Method | 142°F/ 48.9°C TCC |
| Flammable Limits | Not available |
| Auto Ignition Temperature | Not available |
| Decomposition Temperature | Not available |
| Evaporation Rate | 0.1 (n-butyl acetate=1) |
| Partition Coefficient: n-octanol/water | Not available |
| VOC% | 141 g/liter (calculated) |

Section 10: Stability and Reactivity

| | |
|-------------------------|---|
| Chemical Stability | This product is stable and hazardous polymerization will not occur. |
| Materials to Avoid | Strong Oxidizers |
| Conditions to Avoid | None known |
| Hazardous Decomposition | None known |

Section 11: Toxicological Information

The complete toxicological data for each ingredient is unknown and otherwise beyond the scope of this document.

Section 12: Ecological Information

This product is harmful to fish and algae upon immediate exposure.

Section 13: Disposal Considerations

Refer to Sections 5, 6, and 15 for disposal and regulatory information.

Section 14: Transportation Information

DOT Shipping Description Unrestricted/Non-regulated

Section 15: Regulatory Information

TSCA All components are listed on the TSCA.

CERCLA Not reportable

SARA Title III No known reportable ingredients.

Section 16: Other Information

NFPA Rating Health Hazard-1 Fire-1 Reactivity Hazard-0
Key: 4=severe, 3=serious, 2=moderate, 1=slight, 0=minimal

Disclaimer The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person. Proximate cause by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.