## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Chemical Name Mixture CAS No. Mixture

Trade Name COMMODORE TRIM & BUMPER COATING

Product Code SP-550

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)

Automotive care product

Uses Advised Against None

Company Identification Spray Products Corporation

P.O. Box 737

Norristown, PA 19404

Telephone (610) 277-1010 Fax (610) 277-4390

E-Mail (competent person) johnd@sprayproducts.com

**Emergency telephone number** 

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

## **SECTION 2: HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp.

Tox. 1

#### Label elements

Hazard Symbol



Signal word(s)

Hazard Statement(s) Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Precautionary Statement(s) Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing spray.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Wash hands and exposed skin after use.

Keep out of reach of children.

Other hazards None

Revision: September 10, 2014 Page: 1/6

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification		
		426260-76-6	Flam. Liq. 2; H225		
Heptane, branched, cyclic and linear	30 - 60		Asp. Tox. 1; H304		
			Skin Irrit. 2; H315		
			STOT SE 3; H336		
Dranana	10 - 25 74-98-6		10. 35	74.00.6	Flam. Gas 1; H220
Propane	10 - 25	74-96-6	Liquefied gas; H280		
Butane	10 - 25 106-	106-97-8	Flam. Gas 1; H220		
butane		100-97-0	Liquefied gas; H280		

#### Additional Information - None

#### **SECTION 4: FIRST AID MEASURES**



## Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If symptoms develop, obtain

medical attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If symptoms

occur obtain medical attention.

Ingestion Do not give anything by mouth to an unconscious person. Seek medical

treatment.

Most important symptoms and effects, both acute and

delayed

Aspiration of droplets may cause pulmonary oedema.

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

-Suitable Extinguishing Media Extinguis

-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

Do not use water jet.

Special hazards arising from the substance or

mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters A self contained breath

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

Revision: September 10, 2014 Page: 2/6

<sup>\*</sup> The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

Environmental precautions Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None
Additional Information None

## **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No

smoking. Avoid contact with skin and eyes. Use product in a well-

ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place. Store at temperatures not

exceeding 50 °C / 122 °F.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s)

Automotive care product

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## **Occupational Exposure Limits**

		(8hr TWA)		(STEL)		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m <sup>3</sup>			*n-heptane
n-Butane	106-97-8		250 ppm			
Propane	74-98-6	1000 ppm	Aspyx.#			#

<sup>\*</sup>Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C)

**Exposure controls** 

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure

insufficient ventilation, wear suitable respiratory equipment.

limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other) Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection Normally no personal respiratory protection is necessary. In case of



Thermal hazards Not normally required. Use gloves with insulation for thermal

protection, when needed.

Environmental Exposure Controls None known

Revision: September 10, 2014 Page: 3/6

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Liquid / Aerosol Color. Colorless Odor Hydrocarbon Odor Threshold (ppm) Not available pH (Value) Not available Melting Point (°C) / Freezing Point (°C) Not available

Boiling point/boiling range (°C):

Not available
Flash Point (°C)

Evaporation Rate

Not available

Not available

Flammability (solid, gas)

Extremely flammable

2.1% - 9.5% v/v (Propane)

Vapor pressure (Pascal)

Vapor Density (Air=1)

Density (g/ml)

Extremely flammable

2.1% - 9.5% v/v (Propane)

ca. 95 x 10<sup>4</sup> (Propane)

ca. 1.56 @ 0°C (Propane)

Not available

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C)

Decomposition Temperature (°C)

Not available

Not available

450 (Propane)

Not available

Kinematic Viscosity <20

Explosive properties Not explosive.
Oxidizing properties Not oxidizing.

Other information Not available

#### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials Strong oxidizing agents

Hazardous decomposition product(s)``` None known

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Exposure routes: Inhalation, Skin Contact, Eye Contact

### Substances in preparations / mixtures

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

 Acute toxicity
 Oral: LD50 >5 g/kg-bw

 Dermal: LD50 >2 g/kg-bw

Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin

dryness or cracking. May cause eye irritation.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)

LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)

May cause drowsiness or dizziness.

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

Revision: September 10, 2014 Page: 4/6

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity
Reproductive toxicity

There is no evidence of mutagenic potential.

Not available

## **SECTION 12: ECOLOGICAL INFORMATION**

Toxicity - Substances in preparations / mixtures

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term LL50 (96 hour): >13.4 mg/L (Oncorhynchus mykiss)

EL50 (48 hour): 3 mg/l (*Daphnia magna*, mobility)

EC50 (96 hour): 13 mg/l (Pseudokirchnerella subcapitata)

Long Term NOELR (28 days) 1.5 mg/l (Fish) QSAR

LOEC (21 days): 0.32 mg/l (Daphnia magna)

NOEL (96 hour) 6.3 mg/l (Algae)

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

#### **SECTION 14: TRANSPORT INFORMATION**

	U.S. DOT	Sea transport <u>(IMDG)</u>	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

### **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Che	emical Name	CAS No.	Typical %wt.	RQ (Pounds)	
	None				

SARA 311/312 - Hazard Categories:

☐ Fire ☐ Sudden Release ☐ Reactivity ☐ Immediate (acute) ☐ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.	
None			

## SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

Revision: September 10, 2014 Page: 5/6

## California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		

## **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 1-16.

Date of preparation: July 29, 2014

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

#### Hazard Statement(s)

- H220: Extremely flammable gas.

- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.

### Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Revision: September 10, 2014 Page: 6/6